





The "fallitime spelly specials" completion the stage of the building mode, which is the stage of the building mode, which is they seek on the stage of the stage

no high officency and curston. The can be advantaged only in control for long they at well for reporting pagement stanks to be described for long they at well for reporting pagement stanks to be described in control. The "California gents paged in control to the character of the control for control for the control for control for the control for paged in the control for control for the control for c

The invite finish of the ""Statistic swint backets" represents the best of what can be offered in a "great tributa" can amount tide, containable share, informed doors with investable windown, asky reading instrument cluster, well fatted into the death-bested, which is weaker as the content of the content

fully consystendy to its power and scient.

Thanks to its 100 HP obstic engine, the car can be used in the sewn heavy timits as well on though discults for its very high pickup and powerful action as low appeals.

Fig. "Curiette script operate" is also because by its frepaged instruction (get row), air specializate, the airt four property special permits although vision making whilst the airt, property, allows the car to reach the mexicum speed of AU (with 100 match).

this remember operation in the result of power continues with a body of some personality, rate is, the leaster why the car is advantageously used for sporting purposes; as it arrays, needed, for all Alla Zersen cars.





The "Giulietta sprint speciale" completes the range of the Giulietta models, which in their versions of berlina, coupé and spider have won world-wide fame. This model remains in the class of the 1300 cc, class in which the Giuliettas—in their respective category—haven't met any rival regarding the low running costs, the high efficiency and duration. The car


can be advantageously used for long trips as well for sporting purposes thanks to its powerful engine and trouble-free conduct. The "Giulietta sprint speciale" combines the best features of the other models, exalting some of them. For instance the roadability is even better for the lower line of its body and the shorter wheel-base; 5" less than that of the "Giulietta sprint veloce". The efficiency of its brake system, pride of all Alfa Romeo cars, fully corresponds to its power and speed.

The inside finish of the "Giulietta sprint speciale" represents the best of what can be offered in a "gran turismo" car: smooth ride, comfortable seats, trimmed doors with lowerable windows, easy reading instrument cluster, well fitted into the dash-board, which is wadded and covered with an opaque plastic material. The wide and curved windscreen glass and that of the rear window grant a good panoramic view from inside; a large room behind the seats allows arrangement for voluminous luggage. Its heating system is very efficient.

Thanks to its 100 HP elastic engine, the car can be used in the town heavy traffic as well on though circuits for its very high pickup and powerful action at low speeds.

The "Giulietta sprint speciale" is also favoured by its fivespeed transmission (gear-box), all synchronized, the first four forward speeds permit brilliant smooth running whilst the fifth, overdrive, allows the car to reach the maximum speed of 200 Km/h (125 m.p.h.).

This remarkable speed is the result of power combined with a body of acute penetration, this is the reason why the car is advantageously used for sporting purposes; as it occurs, besides, for all Alfa Romeo cars. Alfawiki.nl



The manufacturer has the right to change at any time the specifications without notification, and the figures are approximate and under the best conditions.

Alfawiki.nl

Alfa Romeo s.p.a. - Via Gattamelata, 45 - Milano

Printed in Italy - 1-60 (10) - ILTE Torino

technical features

4
mm 74
mm 75
cc 1290
HP 100
(HP-SAE 116)
7' 5"
4' 3"
4' 2"
13' 6"
5' 5"
lbs 1892
Km/h 200
(m.p.h. 125)
155 × 15
Volt 12

Timing: 2 overhead camshafts driven by a silent double chain.

Clutch: single dry plate, cushioned hub.

Gear-box: 5 synchronized forward speeds and 1 reverse. Ball gear shift lever.

Transmission shaft: in two sections with intermediate bearing flexible joint at gear-box and universal joints at both ends of the second section.

Differential: bevel pinions with hypoid drive.

Front suspension: indipendent wheels with transverse wish-bones, variable spring rate, coil springs and telescopic shock absorbers.

Rear suspension: rigid axle connected to the frame by an upper triangle and two lower struts, coil springs and telescopic shock-absorbers. Variable spring rate.

Steering: left hand driver, by worm and roller.

Brakes: hydraulic 4-wheel brakes, two leading shoes on front; bimetallic drums of large dimensions, front drums fitted with herring bone cooling fins.

UL 8 1

